

FAIRFAX_®

Features

- Metal construction
- One-piece, self-contained ceramic disc valve allows both volume and temperature control
- Temperature memory allows faucet to be turned on and off at any temperature setting
- High-temperature limit setting for added safety
- 2.2 gallons (8.3 L) per minute maximum flow rate
- Lower flow aerator options are available (refer to the Kohler Price Book)
- 5" (12.7 cm) spout reach
- Lever handle
- Touch-activated drain with tailpiece and overflow


Codes/Standards Applicable

Specified model meets or exceeds the following:

- ASME 112.18.1/CSA B125
- IAPMO/UPC
- NSF 61
- Energy Policy Act of 1992
- ADA
- CSA International

SINGLE CONTROL LAVATORY FAUCET **K-12183**

ADA



Colors/Finishes

- CP: Polished Chrome
- PB: Vibrant® Polished Brass
- Other: Refer to Price Book for additional colors/finishes

Specified Model:

Model	Description	Color/Finish		
K-12183	Lavatory faucet with escutcheon ring	□ CP	□ PB	☐ Other
Optional A	ccessories			

PRODUCT SPECIFICATION

Single control lavatory faucet shall be of metal construction. The valve shall be a one-piece, self-contained ceramic disc valve, and allows both volume and temperature control. The valve shall feature temperature memory, allowing the faucet to be turned on and off at any temperature setting, and includes a high-temperature limit stop. Faucet shall have a 2.2 gallons (8.3 L) per minute flow rate. Product shall have lower flow aerator options. Product shall include 5" (12.7 cm) spout, lever handle, and touch-activated drain with tailpiece. Product shall be available with single-hole escutcheon ring. Faucet shall be Kohler Model K-12183-_____.

FAIRFAX_®

Technical Information

Included components: Drain Install this faucet provided.

Installation NotesInstall this faucet following the installation instructions

5" (12.7 cm) 9-15/16" (25.2 cm) 7-3/4" 5-1/2" (19.7 cm) 2-1/2" (14 cm) (6.4 cm) D. 1-3/4" 2-1/4" (4.4 cm) Max (5.7 cm) D. (2.5 cm) D. 16-1/4" 5-1/8" (41.3 cm) (13 cm) 3/8" Compression 1-1/4" Fitting OD 3-13/16" (9.7 cm) **Touch-Activated Drain**

Product Diagram

