QO816L100RBCP

Load center, QO, 1 phase, 8 spaces, 16 circuits, 100A fixed main lugs, NEMA3R, UL, consumer pack





Main

QO
Load Center
Weatherproof enclosure
Surface cover
Curiaco co (ci

Complementary

Complementary		
Tightening Torque	Main lugs 50 lb.in, AWG 8, aluminium/copper Main lugs 50 lb.in, AWG 6AWG 1/0, aluminium/copper	
Load Center Type	Main lugs	
Rated Current	100 A	
Number of Spaces	8	
Max Short Circuit Current Rating	10 kA	
Maximum Number of Single Pole Circuits	16	
Maximum Number of Tandem Breakers	8	
Number of Phases	1 phase	
Voltage Rating	120/240 V AC	
Wire Size	AWG 8AWG 1 aluminium/copper	
Electrical Connection	Lugs	
Grounding Bar	Grounding bar (ordered separately)	
Electrical Connection	Lugs	
Wiring Configuration	3-wire	
Busbar Material	Tin plated aluminium busbar	
Enclosure Material	Welded galvannealed steel	
Cover Finish	Baked enamel Gray	
Box Number	2R	
Height	12.64 in (321 mm)	
Width	8.90 in (226 mm)	

Environment

Enclosure Rating	NEMA 3R outdoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

Ordering and shipping details

Category	01303 - QO MAIN LUG LOAD CENTERS
Discount Schedule	CPQ
GTIN	00047569804779
Nbr. of units in pkg.	1
Package weight(Lbs)	9.76 lb(US) (4.43 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.00 in (12.7 cm)
Package 1 width	10.20 in (25.908 cm)
Package 1 Length	14.30 in (36.322 cm)
Package 2 Weight	809.00 lb(US) (366.956 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
vvarianty	10 11011(13