

Technical Information Sheet



PVC UNIVERSAL PIPE FLASHING

Item Description	Item Number
White	W56PAW1006

DESCRIPTION

Elevate PVC Universal Pipe Flashing is specifically designed for the flashing of round penetrations. PVC Universal Pipe Flashing fits various penetrations from 1" (25 mm) to 4½" (114.3 mm). The Elevate PVC Universal Pipe Flashing must be cut to correct size before installation.

METHOD OF APPLICATION

1. Elevate PVC membrane shall be clear of all dust, dirt and other contaminants prior to installation of the Elevate PVC Universal Pipe Flashing.
2. Penetration shall be clean of foreign material and any old flashing materials.
3. Cut out a circle, above the rib, on the outside of a level ring of the Elevate PVC Universal Pipe Flashing that is smaller than the penetration.
4. Heat-weld the flashing into place and install the clamp and Elevate All Purpose Sealant per current Elevate PVC specifications.

STORAGE

Store material in its original unopened packaging away from sources of physical damage or chemical contamination.

PRECAUTIONS

Do not install over uneven substrates.

LEED® INFORMATION

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Hillside, NJ

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

TYPICAL PROPERTIES

Properties	Value
Material	PVC with DuPont Elvaloy® KEE
Color	White
Clamp	Stainless steel – worm gear type
Pipe Flange	10 ³ / ₄ " (273 mm) diameter
Thickness	0.085" (2.16 mm) ± 10%
Pipe Height	7" (178 mm)
Clamp	Stainless steel, worm gear type

FITS THE PIPE OUTSIDE DIAMETER

1"	25 mm
1 1/2"	38 mm
2"	50 mm
3"	76 mm
4"	102 mm
4 1/2"	114 mm

PRODUCT PACKAGING

Units per Carton	10 Elevate PVC Universal Pipe Flashings - 10 SS Clamps
------------------	--

Please contact Elevate Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.