



# Revel®

## Frameless Sliding Shower Door

### K-707200-L

#### Features

- Frameless, 1/4" (6 mm) thick Crystal Clear tempered glass.
- CleanCoat® technology creates a protective barrier that repels water, prevents dirt and minerals from collecting, and makes it easier to remove hard water spots.

#### Technology

- Center-guided mechanism for smooth, quiet sliding action and easy cleaning.
- Frameless design with minimal metal allows for greater ease of cleaning.
- Contemporary towel bar and knob combination offers storage on the outside of the door without encroaching on the bathing space.
- Low bottom track creates easy entry and exit to the bathing space.
- Out-of-plumb adjustability for simpler installation.

#### Installation

- Sliding shower door.
- Not for use in hospitality.

#### Recommended Products/Accessories

K-23723 Faucet cleaner

#### Included Components

Additional Components:

Hardware kit



#### Codes/Standards

ANSI Z97.1

CPSC 16CFR 1201

#### KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

#### Available Colors/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
-------	------	-------------



SHP	Bright Polished Silver
-----	------------------------



ABZ	Anodized Dark Bronze
-----	----------------------




BNK	Anodized Brushed Nickel
-----	-------------------------

#### Available Glass Options

Code	Description
------	-------------

L	Crystal Clear
---	---------------



## Technical Information

All product dimensions are nominal.

Installation type: For shower base installation

Opening style: Sliding/Bypass

Opening Width - Min: 56-5/8" (1438 mm)

Opening Width - Max: 59-5/8" (1514 mm)

Walk-through - Min: 25-3/4" (654 mm)

Walk-through - Max: 28-3/4" (730 mm)

Base-To-Wall Radius 3/8" (10 mm)

– Max:

Glass thickness: 1/4" (6 mm)

Glass coating: CleanCoat®

## Notes

Install this product according to the installation guide.

Wall jambs are made of clear plastic and may not cover existing shower door holes.

**NOTICE:** The vertical opening should be a minimum of 72-1/2" (1842 mm) to allow clearance for installing the top track over the wall jambs.