Item:
HT-G2LHB-2FT3L-F8155/277-250D
HT-G2LHB-2FT4L-F8210/277-250D
HT-G2LHB-2FT3L-F8155/277-250D-S
HT-G2LHB-2FT4L-F8210/277-250D-S

LED HIGH BAY



SAFETY INSTRUCTION

⚠ WARNING

• To reduce the risk of death, personal injury or property damage from fire, electric shock, falling parts, cuts/abrasions, and other hazards read all warnings and instructions included with and on the fixture box and all fixture labels.
• Before installing, servicing, or performing routine maintenance upon this equipment, follow these general precautions.
• Commercial installation, service and maintenance of luminaires should be performed by a qualified licensed electrician.
• For the installation: If you are unsure about the installation or maintenance of the luminaires, consult a qualified licensed electrician and check your local electrical code.
• To prevent wiring damage or abrasion, do not expose wiring to edges of sheet metal or other sharp objects.
• Do not make or alter any open holes in an enclosure of wiring or electrical components during kit installation.

⚠ WARNING

• Turn off electrical power at fuse or circuit breaker box before wiring fixture to the power supply.
• Turn off the power when you perform any maintenance.
• Verify that supply voltage is correct by comparing it with the luminaire label information.
• All wiring connections should be capped with UL approved wire connectors.

⚠ CAUTION

• Avoid direct eye exposure to the light source while it is on.
• Account for small parts and destroy packing material, as these may be hazardous to children.
• Risk of burn. Disconnect power and allow fixture to cool before changing bulb or handing fixture.
NOTICE: Green ground screw provided in proper location.Do not relocate.
NOTICE: Minimum 90°C supply conductors.
NOTICE: Specifications and dimensions subject to change without notice.
NOTICE: Suitable for Dry or Damp location.

TOOLS REQUIRED

NOTE: Keep your receipt and these instructions for Proof of Purchase.

PACKAGE CONTENT



	PARTS	pcs
A	vhook	2
B	chain	2
C	LED fixture	1

INSTALLATION INSTRUCTION

General Wiring Diagram





INSTALLATION INSTRUCTION

Installation Step:

Always turn off the power supply from main circuit breaker first!
Chain Mounting with V hook
Step1:Clip the brackets to the slots of fixture
Step2:Attach provided V-Hooks to brackets.
Step3:Attach provided chain to the V-hooks and mounting surface.
**NOTE: Purple and Pink lead inside the driver compartment are 0-10V (low voltage) dimming leads.Connect to dimming low voltage wiring only.
• Clean all residues/fingerprints from the new LED high bay and lens. Double check all hanging hardware before moving onto the next installation.

With Motion Sensor-Install sensor (optional)

1.Remove the sensor base cover.



2.Install the sensor adapter.



INSTALLATION INSTRUCTION

3.Install the sensor.



4.The installation is completed.



General Wiring Diagram



WARRANTY

This product is warranted for 5 years from the date of purchase. If this product does not perform to the specifications supplied on this package,send an email to support@runbisonlighting.com for product return and replacement. This replacement is the sole remedy available. Liability for incidental or consecuential damage is expressly excluded.