

SPECIFICATIONS

| | | |
|----------------------------------|--------------------|--|
| Power rating | | 120V~ |
| Frequency | | 60Hz |
| Rated power input | | 1050W (When inlet water temp in 15°C) |
| Seat and dryer temperature range | | 39.4°F~104°F |
| Source water temperature range | | 39.4°F~95°F |
| Water supply type | | DN15(G1/2") |
| Water Inlet | Minimum pressure | 0.08MPa, and also make sure the water flow is above 2.3L/10s |
| | Maximum pressure | 0.75MPa (in a static condition) |
| Toilet | Flush type | Tornado flush |
| | Rough-in | Rough-in 12in |
| Flushing | Way for heating | Transient heating |
| | Temp pf warm water | Off/about 93.2°F~102.2°F (4 levels) |
| | Safety devices | Thermostat series, thermal fuse, flow detection device |
| Warm wind | Warm wind temp | Off/about 95°F~131°F (4 levels) |
| | Wind speed | Above 4m/s (3 levels regulations) |
| | Safety devices | Bimetal thermostat series, thermal fuse |
| Seat ring | Seat ring temp | Off/about 93.2°F~104°F (4 levels) |
| | Safety devices | Thermal fuse |
| Remote control | Dimension | 7.48in(L) * 2.01in(W) * 0.87in(H) |
| | Battery | Two AAA Batteries |
| Power cable length | | Approx. 47.2in |
| Product dimension | | 26.97in(L) * 15.75in(W) * 15.75in(H) |