

ARCHER_{TM}

Features


- Fiberglass (FRP)
- One-piece construction
- For alcove installations
- Removable cover
- Drain hole at center
- 48" (121.9 cm) x 48" (121.9 cm) x 3-15/16" (10 cm)

Codes/Standards Applicable

Specified model meets or exceeds the following:

- CSA B45
- ANSI Z124.1.2





Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Accessories

- CP: Polished Chrome
- PB: Vibrant_® Polished Brass
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Description		Colors/Finishes		
K-9394	FRP shower receptor with removable cover			0	☐ Other
Recomme K-9132	Shower drain		□ CP	□ PB	☐ Other_

Product Specification

The fiberglass (FRP) shower receptor with removable cover shall be 48" (121.9 cm) in length, 48" (121.9 cm) in width, and 3-15/16" (10 cm) in height. Shower receptor shall be for alcove installations. Shower receptor shall be one-piece configuration with drain hole at center. Shower receptor shall be Kohler Model K-9394-_____.

ARCHER_{TM}

Included components:
Removable cover

Technical Information

Fixture*:					
Weight	54 lbs (24.5 kg)				
Configuration	one-piece				
Drain hole	3-3/8" (8.6 cm) D.				
* Approximate measurements for comparison only.					

1062356

Installation Notes

Install this product according to the installation guide.

Shimming may be required to level the fixture.

Shimming may be required between the stud frame and the fixture.

The stud opening tolerance is +1/4" (6 mm), -0" (0 mm).

When fire rated construction is specified, dimensions are to the inside of the fire-rated wall.

