## Wasserman Faucets

## NON-METALLIC DUAL HANDLE UTILITY FAUCET

Includes

1 Utility Faucet 2 SS Supply Lines 2 Mounting Nuts 1 Garden Hose Adapter

## What you will need


- Adjustable Wrench - Safety Glasses (recommended)

## 11053020

Thank you for purchasing this Wasserman® faucet. Anything missing or damaged, please do not return to the place you purchased. Call Toll Free at 1-833-564-5111 and we will send you replacements.

 Turn off water at the supply valve under the sink or at the main water supply, disconnect the supply line, and remove old faucet.


Clean and dry surface area where new faucet will be mounted.



Han


using a flexible braided supply line (4.1) (not included), connect the end with 1/2 in. female IPS to the tailpiece (4.2) of the faucet. Hand tighten. Do not overtighten. Install the other end of the supply line (4.1) to the shut-off valve or supply tube. NOTE: Consumer should follow the directions on the supply line and if you have any questions about proper installation of the supply line, consult the manufacturer of the supply line. NOTE: Do not use plumbers tape on connections, this will void the warranty. If the washer of the supply line is damaged, change to new one before install to the faucet. DO NOT INSTALL SUPPLY LINE WITHOUT INSPECTION. Leakage will come from the supply line and possibly cause water damage to your house.

4. Connect the Water Supply Lines




Position the faucet (A) on the sink surface (2.1).

Hand tighten the mounting nuts (B) to the faucet (A) tailpieces on the underside of the sink (2.1).



 Turn water supply or shut-off valve back on and check for leaks. If leaks occur, tighten nuts slightly.



3. Place weight around the looped hose on the side away from the quick connect (3.1)
Then plug the quick connector cover (3.3) into the faucet body adapter (3.2) by turning around the adapter (3.2)

Pull spray head in and out to check for smooth operation.

