

ULTIMATE FAST GROUT SEAL

SPRAY-ON GROUT SEALER FOR FLOORS,
WALL, BACKSPLASHES, AND MORE



COLOR HOLD TECHNOLOGY

**KEEPS THE GROUT COLOR FROM FADING WHEN APPLIED TO
FRESH/DAMP UNCURED GROUT AS THE GROUT DRIES.**

ULTIMATE FAST GROUT SEAL - Designed for immediate application to damp, uncured floor and wall grout while leaving no hard-to-remove residue, can also be used on clean, existing grout and will not change any surface appearance. Seal immediately after grouting for the ultimate stain protection.

This new **AC Technology** provides unmatched protection for grout, natural stone, masonry and concrete while the "inverted" anyway valve allows for application onto both floor and wall surfaces from a standing position. It penetrates to protect against both oil and water-based stains while still allowing the treated surface to breathe.

EXPECTED WEAR UP TO 25 YEARS!



**GROUT COLOR WON'T FADE WHEN APPLIED TO FRESH GROUT
JUST SPRAY AND WALK AWAY
800 - 1,000 LINEAR FEET
NO CLEAN-UP**

Can be applied to damp/uncured grout immediately after grouting and will keep the grout color from fading while drying and leaves no hard-to-remove residue. Can also be used with clean, existing grout as well. Will not change surface appearance. It penetrates to protect grout, stone and masonry surfaces against both oil and water-based stains.

* This will vary depending on type of surface, wear and proper maintenance. This is not a warranty.

DIRECTIONS

READ BEFORE USING



SHAKE WELL

Always test product in an inconspicuous area to determine suitability for intended use. Suitability for a particular purpose is always the responsibility of the user.

1. Make sure that the surface is thoroughly clean and free from waxes, sealants, or coatings of any kind. Protect acrylic or stained surfaces such as cabinets from overspray when using this product.
2. Shake well. Spray 10-16 inches from surface. Apply product evenly. Wipe off excess if spraying vertical areas.
3. Allow to cure for 24 hours. Test after application using water droplets, if droplets are absorbed, a second or third coat may be necessary to attain the desired performance. Dries to the touch in about one (1) hour at 75°F. Use only in well ventilated areas. Open windows and use fans to circulate air.



- **INSTANT GROUT SEALER**- Just Spray & Walk Away
- **INVERTED TIP**-Specially designed tip allows for precise application onto grout joints without mess
- **4X MORE COVERAGE**-Covers 800-1000 Linear Feet of Grout & Leaves No Hard-to-Remove Residue

HOMEOWNERS AND CONTRACTORS WILL BOTH APPRECIATE THE EASE AND CONVENIENCE OF USING THE ONLY SEALER THAT CAN BE APPLIED IMMEDIATELY AFTER GROUTING. NO NEED TO WAIT HOURS OR DAYS TO FINISH THE JOB.

2212 E. Magnolia St.
Phoenix, AZ 85034

Phone: (480) 499-3145
Email: Info@2GetAdvanced.com



COLOR HOLD TECHNOLOGY



ADVANCED

Sealers & Cleaners with AC Technology