

FlashEdge™ DRIP EDGE

TPO Low Slope Systems

OVERVIEW

FlashCo's FlashEdge TPO Coated Metal Drip Edge is available in standard 2"x4" and 3"x3" profiles, each with a 3/8" kick, angled 30° away from the wall. FlashEdge TPO Drip Edge products are manufactured using 24-gauge, G90 galvanized steel, 40-gauge 3003 H14 aluminum, or 24-gauge 304 stainless sheet that is coated with a layer of .025" non-reinforced TPO. TPO membrane may be welded directly to FlashEdge metal, eliminating the need for adhesive perimeter strips.

**Custom profiles and colors available by request*

APPLICATION

FlashCo's FlashEdge TPO coated Drip Edge is used on single ply roofing systems as perimeter edge metal to prevent moisture intrusion and control the flow of water away from fascia and siding materials as well as helping contain ballast materials on roofing systems that utilize them.

INSTALLATION

Installation of FlashEdge TPO Coated Drip Edge in any form shall be in accordance with the recommendations and specifications of the roofing material manufacturer.

1. Install TPO Coated Metal with 1/8" - 1/4" between adjoining sections.
2. Prepare all welding surfaces by cleaning with TPO membrane cleaner.
3. Heat-weld TPO non-reinforced flashing over joint.
4. Position TPO reinforced membrane and heat-weld to the TPO Coated Metal
5. Apply cut edge sealant (provided by others) along edge of reinforced material.

**Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information intended as a guide and does not reflect the specification range for any particular property of this product.*



GALVANIZED • ALUMINUM • STAINLESS

FEATURES AND BENEFITS

- Allows direct welding of membrane to covering
- Eliminates the need for adhesive stripping
- Available in multiple colors

SAVING THE CONTRACTOR TIME

- **FlashCo's Brand Promise is Speed:** shipping 90% of orders within 3 days.
- 24/7/365 Online Contractor Portal and additional time-saving tools
- Most orders delivered on FlashCo's own delivery trucks
- Get off the roof sooner

STANDARD SIZES & PACKAGING

Size	Qty./Bundle
2" face x 4" on roof (3/8" kick @ 30°)	10 sticks
3" face x 3" on roof (3/8" kick @ 30°)	10 sticks

MATERIALS & COLORS

Material Type	Specification	Colors
.024" Galvanized	G90	White, Gray, Tan, Bronze, Light Gray, Slate Gray (others upon request)
.040" Aluminum	3003 H14	
.024" Stainless	304	