

ITEM	SPECIFICATION
------	---------------

TECHNICAL SPECIFICATIONS

Dimensions	Width: 7.28" (185 mm), Length: 48" (1,219 mm)
Thickness	Overall: 0.236" (6mm) Wear Layer: 0.7 mm (28mil)
Profile	Micro-Bevel Edges
Coverage	24.5 sq.ft (2.28 sq.m) per box 1,225 sq.ft (114 sq.m) per pallet
Planks per Box	10 Planks
Boxes per Pallet	50 Boxes
Weight	43 Lbs. (19.5 kg) per box 2,150 lbs. (975 kg) per pallet
Composition	100% Virgin Premium SPC (Stone Polyvinyl Composite)
Type	Floating-floor with easy-install industry-leading UNilin™ Locking System
Application	Residential & Commercial
Surface Treatment	4x UV Coating, anti-microbial embedded with Ceramic bead Finish
Visual Pattern Repeat	Approx. every 1,200mm (39.37in)
Print pattern repeat	Approx. 1 plank in every 10 boxes
Backing	IXPE Moisture Resistant, Sound Reducing material
Warranty	10 Year Limited Commercial 25 Year Limited Residential

PERFORMANCE

Classification	EN ISO 10582 Domestic Commercial Light Industrial	Heavy Class 23 Very Heavy Class 34 Heavy Class 43	Slip Resistance — Wet	Din 51130	Surpasses
Size & Straightness	EN 426	Passes	Chemical Resistance	EN 423	No Effect
Thickness	EN 428	Passes	Reaction To Fire	EN 13501-1	Bfl-S1 Classification
Dimensional Stability	EN 434	Surpasses	100% Phthalate Free		Yes
Flexibility	EN 435	Passes	100% Waterproof		Yes
Residual Stability	EN 433	Surpasses	Antimicrobial		Yes
Castor Chair	ISO 4918	Passes	Environmental Certification		Floorscore Certified
Color Fastness To Light	ISO 105-B02	Surpasses	Scratch/Abrasion		Excellent
Product-Content Safety	Reach Svhc 163	Passes	Slip Resistance		Class Ds
Formaldehyde Emission	EN 717-1	0 Mg/M	Iic (Impact Isolation Class)	Impact Sound Absorption	72 Db
Slip Resistance — Dry	EN 13893	Surpasses	STC (Sound Transmission Class)	Traveling Sound Absorption	71 Db
			Use With Radiant Flooring		Recommened



LUCIDA®
SURFACES

setting life's stage™

Lucida Surfaces USA

55 Haul Road
Wayne, NJ 07470
+1 (845) 877-7008

Lucida Surfaces Canada

8620 Rue Pascal-Gagnon
Montreal QC H1P 1Z1
+ (514) 587-9926

LucidaSurfaces.com