

FlashJack™ MOLDED PIPE SEAL

TPO Low Slope Systems

OVERVIEW

The Molded TPO Pipe Flashing is an injection-molded, universal component engineered to provide a professional and durable watertight seal for a wide range of pipe penetrations. Developed in conjunction with major roofing system manufacturers, it ensures full compatibility and a superior finish. This flashing is manufactured from premium TPO with an advanced weathering package for exceptional resistance to UV, ozone, and extreme weather. The stepped-rib design allows for easy sizing in the field and ensures the included stainless-steel clamp remains securely in place, providing a more reliable and aesthetic solution than field fabrication.

INSTALLATION

FlashJacks shall be installed in accordance with the recommendations and specifications of the roofing material manufacturer.

1. Prepare all surfaces with a TPO membrane cleaner.
2. Cut the flashing at the appropriate rib for the pipe diameter.
3. Place the flashing over the penetration. Apply water cut-off mastic around the pipe before positioning the flashing.
4. Heat-weld the base flange to the field membrane.
5. Secure the included stainless-steel clamp below the highest rib and tighten until secure.

TECHNICAL DATA AND COMPLIANCE

Property	Test Method	Value
Material		Injection-Molded & Reinforced TPO
Breaking Strength	ASTM D751	> 220 lbf
Tearing Strength	ASTM D751	> 55 lbf
Brittleness Point	ASTM D2137	< -40° (-40°C)
Ozone Resistance	ASTM D1149	Pass (No Cracks)
Heat Aging Resistance	ASTM D573	Excellent

ORDERING INFORMATION

Part Number	Description	Quantity	Box Size	Box Weight
STICN61	Molded TPO Pipe Flashing 1"-6"	10/box	14" X 14" X 12"	~8 lbs



FEATURES AND BENEFITS

- **Universal Design:** Accommodates standard pipes from 1" to 6" in diameter with a single part.
- **Labor Savings:** Saves up to 60% in labor time compared to field-fabricated pipe flashings.
- **Engineered for Performance:** The rib design provides a clear cutting guide and secures the clamp for a lasting seal.
- **Consistent Appearance:** Delivers a clean, uniform, and professional finish to all roof penetrations.
- **Superior Materials:** Injection-molded with high-quality, weldable TPO for reliable, long-term performance.

SAVING THE CONTRACTOR TIME

- **FlashCo's Brand Promise is Speed:** shipping 90% of orders within 3 days
- 24/7/365 Online Contractor Portal and additional time-saving tools
- Most orders delivered on FlashCo's own delivery trucks
- Get off the roof sooner



Our TPO accessories are manufactured to meet or exceed the stringent requirements of ASTM D6878, the Standard Specification for Thermoplastic Polyolefin-Based Sheet Roofing, ensuring proven reliability and system compatibility.

**Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information intended as a guide and does not reflect the specification range for any particular property of this product.*