

# SharkBite Max™

## Braided Connector Hose with Ball Valve

SharkBite Max™ allows users to connect pipe with ease - no tools needed. This new design features a stainless steel retainer for extra strength, higher pressure ratings and a lower insertion effort than previous versions of SharkBite Brass Push-to-Connect fittings. SharkBite Max fittings do not require a PEX stiffener and are compatible with PEX, copper, CPVC, PE-RT and HDPE\*.

### Applications


Residential and commercial potable water, recirculation, hydronic heating/cooling (up to 50% glycol concentration) and direct burial.

### Specifications Data

Materials	
Body	Lead-Free DZR Brass
O-ring	EPDM
Steel Retainer	304 Stainless Steel
Grab Ring	Stainless Steel
Seal Ring	PTFE
Ball	CP Brass or 304 Stainless Steel
Handle	Steel with PVC Coating Stainless
Lock Nut	Steel
Spindle	Lead-Free DZR Brass Stainless
Tube	Steel
Dielectric Ring	POM
Face Seal	EPDM

Pipe Insertion Depth	
Fitting Size	Insertion Depth
1/2 in.	1.00 in.
3/4 in.	1.25 in.

Performance	
Max Working Pressure	
Max Pressure	200 psi
Max Temperature	140°F (60°C)



Dimensions (Inches)			
Part #	Size	A	B
UR3068FX18BV	1/2 in. X 3/4 in. FIP	18.0	2.1
UR3088FX18BV	3/4 in. X 3/4 in. FIP	18.0	2.4

### Certifications & Listings

ASME A112.18.6/CSA B125.6, ASME A112.4.14/CSA B125.14\*\*, NSF/ANSI 14, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372

\* HDPE installations must use a tube stiffener. Sold separately by HDPE manufacturer.

\*\*Ball Valve

For listing information, please contact Customer Service

US 1-877-700-4242 | [sharkbite.com](http://sharkbite.com)  
Canada 1-888-820-0120 | [canadasales@rwc.com](mailto:canadasales@rwc.com)

Product Submittal	
Name	
Date	
Architect/Owner	
Contractor	
Tag	
Notes	

Rev 2.0 / 03-10-25