

SharkBite Max™

Water Heater Kit

SharkBite Max™ allows users to connect pipe with ease - no tools needed. This new design features a stainless steel retainer for extra strength, and a lower insertion effort than previous versions of SharkBite Brass Push-to-Connect fittings. SharkBite Max fittings do not require a PEX stiffener and are compatible with PEX, copper, CPVC, PE-RT and

Applications

Monitors water pressure in residential and commercial systems. Ideal for troubleshooting and maintaining potable water, recirculation, and hydronic heating/cooling systems (up to 50% glycol). Requires an accessible location for easy reading andmaintenance.

Specifications Data

Materials	
Body	Lead-Free DZR Brass
O-ring	EPDM
Steel Retainer	304 Stainless Steel
Grab Ring	Stainless Steel
Seal Ring	PTFE
Ball	CP Brass or 304 Stainless Steel
Handle	Steel with PVC Coating Stainless
Lock Nut	Steel
Spindle	Lead-Free DZR Brass Stainless
Tube	Steel
Dielectric Ring	POM
Face Seal	EPDM

ASME All2.18.6/CSA Bl25.6, ASME All2.4.14/CSA Bl25.14**, NSF/ANSI 14, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372

* HDPE installations must use a tube stiffener. Sold separately by


Pipe Insertion Depth		
Fitting Size	Insertion Depth	
1/2 in.	1.00 in.	
3/4 in.	1.25 in.	

HDPE manufacturer.

**Ball Valve

Certifications & Listings

Performance		
Max Working Pressure		
Max Pressure	200 psi	
Max Temperature	180° F (60°C)	



Part # UR24680

Kit includes:

- (1) 3/4 in. FIP x 3/4 in. SharkBite Max 18 in. Corrugated Water Heater Connector (URSS3088FX18)
- (1) 3/4 in. FIP x 3/4 in. SharkBite Max 18 in. Corrugated Water Heater Connector with Ball Valve (URSS3088FX18BV)
- (1) 3/4 in. Disconnect Clip (U712)

Dimensions (Inches)			
Part #	Size	А	В
URSS3088FX18BV	3/4 in. X 3/4 in.	18.0	2.4
URSS3088FX18	3/4 in. X 3/4 in.	18.0	1.3

Product Submittal		
Name		
Date		
Architect/Owner		
Contractor		
Tag		
Notes		



For listing information, please contact Customer Service