HOM3060L225PGCVP

Load center, Homeline, 1 phase, 30 spaces, 60 circuits, 225A convertible main lugs, PoN, NEMA1, gnd bar, value pack





Main

Product Type	Load Center value pack
Marketing Trade Name	Homeline
Load Center Type	Main lugs
Rated Current	225 A
Number of Spaces	30
Number of Circuits	60
Enclosure Rating	NEMA 1 for indoor installation
Cover Type	Combination flush/surface cover
Electrical Connection	Lugs
Included Options	Grounding bar 1) Circuit breaker 3) 1P 20 A 120/240 V AC Circuit breaker 2) 2P 30 A 120/240 V AC

Complementary

Short Circuit Current Rating	10 kA
Number of Tandem Breakers	30
Number of Phases	1 phase
Rated Operational Voltage	120/240 V AC
Wire Size	AWG 4250 kcmil copper AWG 4300 kcmil aluminium
Wiring Configuration	3-wire
Cover Finish	Gray baked enamel
Busbar Material	Tin plated aluminium busbar
Enclosure Material	Welded sheet steel
Surface Finish	Baked enamel Gray
Box Number	10
Height	33.78 in (858 mm)
Width	14.25 in (362 mm)
Depth	3.74 in (95 mm)

Environment

Ambiant Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL E-6294

Ordering and shipping details

00185 - MISC. HOM LOAD CENTERS
DE3C
00785901977230
1
33.2 lb(US) (15.06 kg)
Yes
US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	56.00 in (142.24 cm)
Package 1 width	163.00 in (414.02 cm)
Package 1 Length	364.00 in (924.56 cm)
Package 2 Weight	598.00 lb(US) (271.248 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant [₫] EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile