

QO120DFC

Mini circuit breaker, QO, 20A, 1 pole, 120 VAC, 10 kA, dual function, pigtail, plug in mount, clam pack



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	20 A
Voltage Rating	120 V AC
Mounting Type	Plug-in
Number of Poles	1P
Circuit Breaker Type	Combination ARC-fault and ground fault
Ratings	Not rated
Electrical Connection	Pressure plate
Type of packing	Clam packaging

Complementary

Interrupt Rating	10 kA 120 V AC 50/60 Hz
Number of Panel Spaces	1
Wire Size	AWG 14...AWG 8 copper AWG 14...AWG 10 aluminium
Tightening torque	40.71 lbf.in (4.6 N.m)
Maximum Height	4.75 in (120.65 mm)
Maximum Depth	2.91 in (73.91 mm)
Maximum Width	0.75 in (19.05 mm)

Environment

Certifications	UL Listed CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	01318 - QO 1 POLE BULK BRKRS.
Discount Schedule	CPQ
GTIN	00785901401681
Nbr. of units in pkg.	1
Package weight(Lbs)	0.65 lb(US) (0.29 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	8.00 in (20.32 cm)
Package 1 width	1.50 in (3.81 cm)
Package 1 Length	4.50 in (11.43 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	3
Package 2 Weight	31.20 oz (884.504 g)
Package 2 Height	8.40 in (21.336 cm)

Package 2 width	4.30 in (10.922 cm)
Package 2 Length	4.90 in (12.446 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information